(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 22 September 2005 (22.09.2005)

PCT

(10) International Publication Number WO 2005/087537 A1

(51) International Patent Classification⁷:

B60N 2/48

(21) International Application Number:

PCT/GB2005/000966

(22) International Filing Date: 11 March 2005 (11.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0405716.2 13 March 2004 (13.03.2004) GB 0405717.0 13 March 2004 (13.03.2004) GB

- (71) Applicant: BRITAX EXCELSIOR LIMITED [GB/GB]; 1 Churchill Way West, Andover, Hampshire SP10 3UW (GB).
- (71) Applicant and
- (72) Inventor: DAVID, Shaun, Carine [GB/GB]; c/o Britax Childcare Limited, 1 Churchill Way West, Andover, Hampshire SP10 3UW (GB).
- (74) Agent: NIGEL BROOKS CPA; Hill Hampton, East Meon, Petersfield, Hampshire GU32 1QN (GB).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GO, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: SAFETY SEAT



(57) Abstract: A deformable, polypropylene-moulding lining (11), is provided in a head rest. It has a crosspiece (12), clipped (14) to the head support (5) and right and left deformable wings (15, 16). These are longer than the support wings (5, 6) of the head part (4), extending past distal edges (17) of the support wings. The deformable wings are spaced inwards from the support wings, with voids (18) defined between them. The deformable wings are divided into two in their forwards extent by a living hinge (19) into a front portion (20) and a rear portion (21). The living hinge is positioned just inside the distal edges of the shell wings. The injection moulded lining has its own foam materiel lining (22), the whole being covered with upholstery (23). The result of the arrangement is that if an occupant's head H impacts the lining in side impact of the vehicle equipped with the seat, the relevant lining wing will be pressed against the shell wing. This involves energy absorbing (maximum acceleration limiting) deformation of not only the foam material, but also of the lining wing and to a less extent of the shell wing. With the lining wing deformation (24), the front portion (20) of the lining wing pivots forwards about the shell edge (17), from a position swept back with respect to the shell wing to a position generally in line with the compressed inner portion of the lining.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.